

IN THE CLAIMS:

The current claims follow. For claims not marked as amended in this response, any difference in the claims below and the previous state of the claims is unintentional and in the nature of a typographical error.

1. (Currently Amended) A method for determining feature data that represents information about the shape of an object (o), the object (o) being located in a k -dimensional space, the method comprising the steps of:

determining, by a computer, a partitioning scheme (RP , RP) that defines a plurality of cells (ϕ) in the space in which the object (o) is located such that at least some of the cells (ϕ) each contain a respective portion of the object (o), and

determining, by the computer, the feature data for the object (o) on the basis of at least one property of the respective portions of the object (o) that are contained in the plurality of cells (ϕ), ~~the method being characterized in that~~ wherein at least two of the plurality of cells (ϕ) overlap each other at least in part.

2. (Currently Amended) The method of claim 1, characterized in that the plurality of cells (ϕ) comprises at least a first and a second group of cells ($gi.sub.1, gi.sub.2, go.sub.1, go.sub.2$) such that the union of the cells in the first group of cells ($gi.sub.1, go.sub.1$) coincides with the union of the cells in the second group of cells ($gi.sub.2, go.sub.2$), wherein each cell of the first group of cells ($gi.sub.1, go.sub.1$) overlaps at least in part with at least one respective cell of the second group of cells ($gi.sub.2, go.sub.2$).

3. (Currently Amended) The method of claim 1 or claim 2, characterized in that the plurality of cells ($\{c_i\}$) comprises at least a group of nested cells ($\{g_n\}$), wherein all cells of the group of nested cells ($\{g_n\}$) are nested within each other.

4. (Currently Amended) The method of claim 3, characterized in that the cells of the group of nested cells ($\{g_n\}$) form a sequence in which the k -dimensional volume of the respective portions of the object (o) that are contained in the cells of the group of nested cells ($\{g_n\}$) increases in an ~~at least approximately~~ a substantially regular manner.

5. (Currently Amended) A method for determining feature data that represents information about the shape of an object (o), the object (o) being located in a k -dimensional space, the method comprising the steps of:

determining a partitioning scheme (DP, RP) that defines a plurality of cells ($\{c_i\}$) in the space in which the object (o) is located such that at least some of the cells ($\{c_i\}$) each contain a respective portion of the object (o), and

determining the feature data for the object (o) on the basis of at least one property of the respective portions of the object (o) that are contained in the plurality of cells ($\{c_i\}$),
~~the method being characterized in that wherein~~ the partitioning scheme (DP, RP) is determined such that at least some of the boundaries of the cells ($\{c_i\}$) defined by the partitioning scheme (DP, RP) are adapted to the individual shape of the object (o) to delimit a plurality of regions ($\{r_i\}$) in the space in which the object (o) is located such that the respective portions of the object (o) that are contained in the plurality of regions ($\{r_i\}$) are approximately equal to each other with respect to a predetermined measurement metric.

6. (Currently Amended) The method of claim 5 ~~and one or~~ any of claims 1 to ~~to~~ to 4.

7. (Currently Amended) The method of claim 5 or claim 6, characterized in that at least one region $\langle r \rangle$ of the plurality of regions $\langle r \rangle$ contains at least two cells $\langle p \rangle$ of the plurality of cells $\langle p \rangle$ that overlap each other at least in part.

8. (Currently Amended) The method of one of claims 5 to 7, characterized in that all regions $\langle r \rangle$ of the plurality of regions $\langle r \rangle$ are disjoint with respect to each other.

9. (Currently Amended) The method of one of claims 5 to 8, characterized in that the measurement metric, for each region $\langle r \rangle$ of the plurality of regions $\langle r \rangle$, is the k -dimensional volume of the respective portion of the object $\langle o \rangle$ contained in this region $\langle r \rangle$.

10. (Currently Amended) The method of one of claims 5 to 9, characterized in that each region $\langle r \rangle$ of the plurality of regions $\langle r \rangle$ corresponds to the union and/or difference and/or intersection of at least two cells $\langle p \rangle$ of the plurality of cells $\langle p \rangle$ or to exactly one cell $\langle p \rangle$ of the plurality of cells $\langle p \rangle$.

11. (Currently Amended) The method of one of claims 5 to 10, characterized in that at least some of the regions $\langle r \rangle$ of the plurality of regions $\langle r \rangle$ represent k -dimensional spheres and/or k -dimensional shells and/or sectors of k -dimensional spheres and/or sectors of k -dimensional shells in the space in which the object $\langle o \rangle$ is located.

12. (Currently Amended) The method of one of claims 1 to 11, characterized in that at least some of the cells $\langle p \rangle$ defined by the partitioning scheme $\langle DP, RE, RP \rangle$ represent k -dimensional spheres and/or k -dimensional shells and/or sectors of k -dimensional spheres and/or sectors of k -dimensional shells in the space in which the object $\langle o \rangle$ is located.

13. (Currently Amended) The method of one of claims 1 to 12, characterized in that the feature data for the object (e) is determined on the basis of the k -dimensional volume of each respective portion of the object (e) contained in each cell (p) of the plurality of cells (p) and/or on the basis of data defining the k principal axes of each respective portion of the object (e) contained in each cell (p) of the plurality of cells (p) .

14. (Currently Amended) ~~Use of a~~ The method according to one of claims 1 to 13 for performing a similarity search between claim 1, wherein the determining steps are performed first for a first object and then also performed for a set of second objects, wherein to determine feature data for the first object and for each of the set of second objects, is determined according to the method according to one of claims 1 to 13, and wherein the and further comprising performing a similarity search is performed between the first object and the set of second objects based on the basis of a comparison of the determined feature data.

15. (Currently Amended) ~~Use of a~~ The method according to one of claims 1 to 13 for performing a similarity classification of a set of objects, claim 1, wherein the determining steps are performed to determine feature data for each object of the a set of objects is determined according to the method according to one of claims 1 to 13, and wherein the objects of the set of objects are grouped according to their respective similarities on the basis of a classification of the determined feature data.

16. (Currently Amended) ~~Computer program product comprising~~ A non-transitory computer-readable medium encoded with executable program instructions for execution by at least one processor, wherein the program instructions cause the at least one processor to perform or use a method according to one of claims 1 to 15.

17. (Currently Amended) Apparatus comprising at least one processor, wherein the apparatus is adapted for performing or using configured to perform a method according to one of claims 1 to 15.